



GP100M ELECTRIC 4"

Super Super silenced, automatic self-priming pump unit.
Fully bunded unit. Lifting eye. Forklift pockets.
Max solids passage 44 mm.
100mm inlet and outlet c/w PN 10 flanged inlet and outlet couplings.
Max working pressure 4 Bar.
Max Flow: 180 m³/hr.

FEATURES

If power is available on site use it for pumping.
Its Super silenced running makes it ideal for urban areas (much quieter than the Wispa).
It will out preform the Gp100M diesel.
Max working head: Gp100M25 Diesel with packing holder. 2.8 bar.
Electric: 4 bar.
Max flow Diesel: 162 m³/hr.
Electric: 180 m³/hr.
Suitable for all pumping applications.
One pump for high flow and low flow applications (ideal for flushing).
Complete control over flow and pressure.
Super Green pump unit.
No Fumes.
45 KVA generator will start and run it.

Variable speed drive panel.
Motor speed controlled from 1000rpm-2000rpm. Manual control using a potentiometer. Hand off auto switch.
Run and trip lights.
Emergency stop button.
Easy plug in float switch option.
63 amp socket for power connection.
The unit must be hired with Silflex extension lead
Manual change over for flooded suction by closing two lever valves.
Oil Lubricated mechanical seal in case of dry running.
35 k.w. 400vt 3 phase motor.
55 amps max.
Super silenced operation.
Transducer fitted for automatic maintaining of delivery pressure.
This must be pre-set.

PERFORMANCE CURVE

