

## MIZAR 60 SUBMERSIBLE PUMP

Submersible electric pumps for white, dirty water and aggressive liquids drainage



### FEATURES

Rain, seepage, sump pit and catch tank water pump out.

Garden and vegetable-garden mini flood irrigation system rainwater catch tank pump down.

White water pump over from reservoirs and vats.

Pumping dirty water with possible floating solid contents (only VOX series).

Pumping aggressive liquid.

Semi wet motor watercooled.

Double mechanical seal: double sealing ring-engine face, oil bath mechanical seals pump face

Permissible draught of water: 5 m.

IP68 protection class.

Class "F" insulation.

Max. pumped liquid temperature: 35°C.

Versions:

Single phase: 220-277V/50Hz or 220-277V/60Hz with built in thermal protection and permanent capacitor.

Standard cable features:

Single phase: 10 metres H05VV-F for the standard version (automatic-manual).

### TECHNICAL

Pump head ..... : 8,0 mt ÷ 10,0 mt

Delivery ... : 9,0 m<sup>3</sup>/h ÷ 10,5 m<sup>3</sup>/h

Rated horsepower .. : 0,25 kW

(0,33 HP) ÷ 0,45 kW (0,6 HP)

Solid matter bypass up to 10 mm (serie VOX 20 mm)

### PERFORMANCE CURVE

